

Black Body Sources

Dual Black Body Calibration System

Space Saver Calibrator for Simultaneous Measurement of Low & Medium Temperatures

Basic Accuracy : $\pm 0.5\%$ F.S.

For Non-contact Pyrometer Calibration

Model

CN-DT

- Enables simultaneous measurement of 2 Pyrometers / Quick Measurement in 2 Points over the range
- Compact, Light Weight, Bench-top & Portable
- Dual Ranges : 50 to 300°C & 250 to 600°C
- Excellent Accuracy & Stability
- High Emissivity, wide Aperture
- Auto-tune PID Controller
- Low Power Consumption
- Cost effective – Best Value for Money
- RS-232 Computer Interface – Optional
- Calibration Management Software – Optional



P.T.O

SPECIFICATIONS

Models	Chamber 1	Chamber 2
Range	50 to 300°C	250 to 600°C
Accuracy	Within 0.5% of indicated temperature (Min. 1°C)	Within 0.5% of indicated temperature (Min. 2°C)
Stability	±0.5°C	
Resolution	0.1°C	
Temperature Control	Auto-tune PID Controller	
Heating time (to max.)	45 Minutes	
Stabilization time	30 minutes	
Temperature Readout	°C / °F selectable	
Emissivity	0.98	
Aperture size	φ 25 mm	
Power Supply	230 VAC / 50 Hz	
Dimension	450 x 410 x 190 mm (W x D x H)	
Weight	14 Kgs	
Housing / Mounting	Bench-top / Table-top (Portable)	

STANDARD DELIVERY
<ul style="list-style-type: none"> • Basic Instrument • Mains Cable • Spare Fuses • Traceable Calibration Certificate • Instruction Manual

OPTIONAL
<ul style="list-style-type: none"> • RS-232 Computer Interface • "Caltemp" Calibration Software • Contact Thermocouple (to measure cavity temperature) • Calibration Certificate from NABL Accredited – as per ISO/IEC 17025:2005 Laboratory

